

Custom Cabinet Form



Please fill out one Quote Form for EACH style cabinet ordered

Create a custom safety cabinet to meet your specific storage requirements. Constructed from 18-gauge cold-rolled steel, custom cabinets have all the features of Justrite's leading safety cabinets, including U-Loc™ door handle, SpillSlope® safety shelves, and a rugged welded design. All cabinets meet NFPA Code 30 and OSHA 29 CFR 1910.106 for the storage of flammable liquids. Cabinets with self-closing doors also meet the International Fire Code.

Cabinets with self-closing doors and proper warning labels comply with NFPA 1, NFPA 400, and the IFC for the storage of hazardous materials such as acids, bases, flammable solids, oxidizers, and more.

All cabinets are designed for indoor use and backed by a ten-year warranty.



FM Approvals is an independent third party certification organization which objectively tests property loss prevention products and certifies those that meet rigorous loss prevention standards. The FM Approved mark tells you that Justrite's products conform to the highest standards and will perform as expected. Many companies mandate the use of FM-approved products for insurance and other reasons.

Specify your requirements using the form on the following pages with as much detail as possible. **Complete all 3 pages and submit this form using the instructions on page 3. A Justrite representative will respond within one business day.**

Design Considerations

Define the type of hazardous liquids to be stored. If several types are to be stored, segregation may be required.

Measure the available space. Evaluate workstation access to the storage site and traffic flow through that area.

Determine the amount of storage capacity needed for each location. Consider the type of containers to be stored and how much shelf space and clearance height is needed. If large vessels such as 55-gallon (200-liter) drums are going to be stored, be sure to allow room for dispensing apparatus. Keep in mind that OSHA limits the storage of Category 1, 2 or 3 flammables to not more than 60-gallons (227-liters), nor more than 120-gallons (454-liters) of Category 4 flammables, per cabinet.



Step 1: Cabinet Basics

PLEASE COMPLETE BEFORE CONTINUING TO PAGE TWO

How many cabinets needed with these specifications? Quantity _____

Height dimensions are measured from the sidewall of the cabinet and do not include the leg levelers installed and extended at 5/8". All dimensions are nominal. Manufacturing tolerances are approximately 1/16".

Specify cabinet size

Height _____ in inches (max. height is 72-in (1829-mm), minimum height is 19-in (483-mm), or 23-in (584-mm) if recessed kickplate option is chosen on page 2.)

Width _____ in inches (max. width is 60-in (1524-mm), minimum width is 18-in (457-mm))

Depth _____ in inches (max. depth is 48-in (1219-mm), minimum depth is 18-in (457-mm))

Door quantity is determined by the width of the cabinet

If cabinet is less than 28-in (711-mm) wide, it will have one door. Choose one hinge location. Right hinge Left hinge

If cabinet is greater than 28-in (711-mm) wide, it will either have two doors or one pair of bi-fold doors.

(Select door style in the next section.)

CABINET OPTIONS

Recessed Kickplate. Choose when additional space for toes is needed (typically used in conjunction with undercounter applications).

Door Style. Manual-closing doors are the most economical. Self-closing doors add an extra measure of protection and are required in many areas. Sliding, self-closing doors are ideal for tight areas. Please check with authority having jurisdiction for local requirements.

Color. See below for color standards or choose the one that best suits your needs.

Label. Select application specific labels.

Shelf Quantity. One SpillSlope® galvanized steel shelf is included with each cabinet. Additional shelves may be ordered. Load rating for shelves is 350-lb (151-kg) each.

Poly Trays for Shelves and Sump.

Removable polyethylene trays are recommended for highly corrosive liquids.

Vents. Check with your local authority having jurisdiction to determine if your application requires venting. If vents are required, choose a preferred location. Note: Standard vent protocol is two vents, diametrically opposed on each side of the cabinet, or on the back. Vents have integral flash protection.

ChemCor® Lining. 100% seamless liner on all interior walls, ceiling, sump, inside doors and shelves protects exposed cabinet surfaces from corrosion.

Step 2: Select Your Cabinet Options

Recessed kickplate No kickplate 4-in (102-mm) H x 3-in (72-mm) D kickplate Other H _____ x D _____ (inches)

Door Style Manual Self-Closing
 Sliding (Available only on cabinets 34-in (864-mm) or 43-in (1092-mm) wide and are provided in pairs.)

Color Yellow Red White Silver Light Neutral Blue Green Orange
 Royal Blue Other _____ Color variations not listed can be handled on a case-by-case basis.

Label Flammable - Keep Fire Away Flammable Waste Acid Pesticide Emergency
 Hazardous Material - Keep Fire Away
(If checked, the following label pack will be included from which the user can choose their specific application.)
 • Pyrophoric • Oxidizer • Self-Reactive • Toxic • Water-Reactive • Acid • Base • Corrosives • Flammable Solid • Organic Peroxide

Additional shelves No Yes, Quantity _____ (One galvanized SpillSlope® steel shelf is included with each cabinet.)
 Quantity, Half-depth shelf _____

ChemCor® lining No Yes

Polyethylene trays for shelves No Yes, Quantity _____ **Polyethylene tray for bottom sump** No Yes

Vents None One on each side Two on back Other _____



Choose from nine great paint colors:



*Coordinates with Sure-Grip® EX Cabinets for corrosives.
 **Coordinates with Sure-Grip® EX Hazardous Material Cabinets

Custom Cabinet Form



Do you require FM approval? Yes No

Note: FM approval on your cabinet depends on size and design specifications and may incur additional costs. Justrite evaluates each custom safety cabinet submission to determine FM approval feasibility. End user will be advised of complete build specifications prior to ordering. FM approval is NOT GUARANTEED. (For more information about the FM Approved mark, [click here.](#))

Shipping Domestic (US and Canada) International (Cabinets are shipped on ISPM 15 pallets)

Desired date of delivery _____

(Additional charges may apply. Lead time varies depending on specifications and quantity.)



NOT SURE WHAT I NEED. WE'RE HAPPY TO HELP
IF YOU HAVE QUESTIONS OR WANT TO PROVIDE ADDITIONAL INSTRUCTIONS.

REQUIRED INFORMATION:

Distributor:

Account No. _____

Company Name _____

Name _____

Email _____ Phone _____

Justrite sells only through authorized distributors.

Custom cabinet orders are non-cancelleable and non-returnable. Price quoted is F.O.B. Mattoon, Illinois 61938

End User:

Company Name _____

Name _____

Email _____ Phone _____

For Internal Use Only:

Date _____

Justrite Quote No. _____

Justrite Order No. _____

Business Development Specialist _____

Cabinet Part No. _____

FM Approved Yes No

I have reviewed this order form for correctness.

Signature required below upon approval of quote.

Engineering _____

Business Development _____

End User _____

[Click Here](#) to submit via email to Justrite Business Development
("Click Here" button will prompt you to choose email preference)

Fax: 1-800-488-5877 Email: bds@justritemfg.com