

# NoTrax<sup>®</sup> Floor Mats With RedStop<sup>™</sup> Technology

Unique to NoTrax<sup>®</sup> floor mats, RedStop<sup>™</sup> anti-slip technology dramatically reduces mat slippage on smooth surfaces, such as tile or sealed/treated floors. RedStop provides increased friction between the underside of the mat and a clean, dry floor surface to anchor the mat in place without leaving a tacky or sticky residue.

We're confident you will find the performance of this floor mat to be second to none. To ensure that you get the best possible performance from your mat and to maintain its appearance and integrity over the longest possible time, follow these care tips.

## Getting Started

After removing the mat from the box, it should lay flat in a warm, dry environment for several hours to allow it to relax and uncurl before placing it into service.

## Care and Cleaning

When placing a mat into service, be certain that the floor and the underside of the mat are completely free of dirt and debris. For best results, periodically clean the bottom of the mat using a damp cloth only, NO cleaning chemicals. Allow to air dry after cleaning. If using the mat on cleaned carpet, make sure that the carpet is completely dry before returning mat to use.

NoTrax will not be liable for any injuries resulting from failure to follow the recommended housekeeping procedures. Frequent cleaning under the mat is also required to maintain the warranty.



## Storage and Handling

For proper storage, roll the mat with the top surface facing out and lay flat. Do not stack any materials or other mats on top of a rolled mat. Store mats in a dry environment with a moderate temperature.

**Note:** Matting must never be stored on-end. This will cause the edges to curl and will void the warranty.